

The above lights are designed for use on sail or power driven vessels under 20 meters (65.6 ft.) in length operating on a nominal 12 volt system. All previous certifications apply. In order to comply with the '72 COLREGS\* and the U.S. Inland Rules\*, the following must be adhered to:

### MOUNTING INFORMATION

Read all instructions before proceeding.

- 1). These instructions show the orientation of the light after the proper location has been determined. For proper light selection, positioning and configuration, refer to the A.B.Y.C. Standard A-16\*, the '72 COLREGS\*, and the U.S. Inland Navigation Rules\*.
- 2). This light is supplied with the proper bulb for operation on a nominal 12 volt system . Use PERKO Cat. No. 0070DP0CLR, 12V, 10W bulb for a 12 volt system (Stern Light Cat. No. 093900112V or 0939DP112V).
- 3). These Lights are designed to be mounted on a vertical surface that is perpendicular to the centerline of the boat and facing astern.
- 4). Draw an 8 inch long horizontal reference line through the center of the selected mounting location.
- 5). Cut out the mounting template below. Tape it on the mounting surface such that the reference line (drawn above) passes through the exact center of the template.
- 6). Drill two holes through the template as indicated for the mounting screws.
- 7). Drill a 2-1/8 inch hole to accommodate socket holder as indicated.
- 8). Attach supply connections to the light, making sure to wire in accordance with both A.B.Y.C. Standard E-9\* and U.S. Coast Guard Safety Standards for Boat Electrical Systems (33 CFR 183)\*

\* The above referenced standards can be obtained from:

1). American Boat & Yacht Council, Inc.  
613 Third Street, Suite 10  
Annapolis, MD 21403

2). U.S. Coast Guard  
Washington, D.C. 20593  
(or your local C.G. office)

PERKO, INC.  
16490 N.W. 13th. Avenue  
Miami, FL 33169-5707  
www.perko.com

08/14  
0939INS1

### MOUNTING TEMPLATE

